



# **trutex**

*digital printing textiles*

Mehmet Nesih Özmen Mh. Savur Sk. No:22  
Merter - Güngören - İstanbul / Turkey  
P. +90 212 637 76 68 | F. +90 212 637 03 38



Micro Satin / Trutex 102

**trutex**  
digital printing textiles



**trutex**  
digital printing textiles

## MICRO SATIN / Trutex 102

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	155 gr/m <sup>2</sup> (± 5%)
WIDTH	152-255-310 cm
WHITENESS	>130
TYPE	Latex / Sublimation Transfer / Sublimation Direct
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B / M1*
APPLICATIONS	Lightbox, Display Frame Systems

Latex

SUB  
Direct

SUB  
Transfer



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



**DSP 180 / Trutex 104**

**trutex**  
digital printing textiles



**trutex**  
digital printing textiles

## DSP-180 / Trutex 104

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	185 gr/m <sup>2</sup> (± 5%)
WIDTH	315 cm
WHITENESS	>130
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Display frame system, Advertising banner

Latex


SUB  
Direct

SUB  
Transfer



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.





## DSP-210 / Trutex 105

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	210 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>140
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Display frame system, Advertising banner



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.



**Rapido -FR / Trutex 107**

**trutex**  
digital printing textiles



**trutex**  
digital printing textiles

## RAPIDO -FR / Trutex 107

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	190 gr/m <sup>2</sup> (± 5%)
WIDTH	160 - 260 - 320 cm
WHITENESS	>100
TYPE	UV / Latex / ECO Solvent / Sublimation Transfer
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems, Pop-up Display Systems, Blow-ups



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



Rapido / Trutex 108

**trutex**  
digital printing textiles



**trutex**  
digital printing textiles

## RAPIDO / Trutex 108

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	190 gr/m <sup>2</sup> (± 5%)
WIDTH	160 - 260 - 320 cm
WHITENESS	>100
TYPE	UV / Latex / ECO Solvent / Sublimation Transfer
APPLICATIONS	Lightbox, Display Frame Systems, Outdoor, Blow-ups



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.


Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.





## Micro Satin Universal / Trutex 109



### MICRO SATIN UNIVERSAL / Trutex 109

#### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	165 gr/m <sup>2</sup> (± 5%)
WIDTH	310 cm
WHITENESS	>120
TYPE	UV / Latex / Sub. Direct / Sub.Transfer
APPLICATIONS	Lightbox, Display Frame Systems



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited


The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



## Micro Double Satin / Trutex 111



### MICRO DOUBLE SATIN / Trutex 111

#### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	250 gr/m <sup>2</sup> (± 5%)
WIDTH	310 cm
WHITENESS	>145
TYPE	Sublimation Transfer / Sublimation Direct
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems, Projection Front

SUB  
Direct

SUB  
Transfer



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job  
The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.





Elasto / Trutex 112



## ELASTO / Trutex 112

### TECHNICAL SPECIFICATIONS


COMPOSITION	100% Polyester
WEIGHT	245 gr/m <sup>2</sup> (± 5%)
WIDTH	310 cm
WHITENESS	>130
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Elastic Decoration, Chair Covers, Covering curved frame, Tension Systems



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.



Premium Canvas / Trutex 113



## PREMIUM CANVAS / Trutex 113

### TECHNICAL SPECIFICATIONS

COMPOSITION	55% Cotton, 45% Polyester
WEIGHT	310 gr/m <sup>2</sup> (± 5%)
WIDTH	310 cm
WHITENESS	>85
TYPE	UV / Latex
APPLICATIONS	Framed artwork, art reproduction



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.


Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.





Flash Ultra / Trutex 120



## FLASH ULTRA / Trutex 120

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	210 gr/m <sup>2</sup> (± 5%)
WIDTH	260-310-320 cm
WHITENESS	>130
TYPE	UV / Latex / Sublimation Direct
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems




\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job  
The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.





## Blackback Soft / Trutex 123



### BLACKBACK SOFT / Trutex 123

#### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	240 gr/m <sup>2</sup> (± 5%)
WIDTH	160-260-320 cm
WHITENESS	>90
TYPE	UV / Latex / ECO Solvent
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Frame systems with black backside



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited


The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



Photo 185 / Trutex 124



## PHOTO 185 / Trutex 124

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	185 gr/m <sup>2</sup> (± 5%)
WIDTH	315 cm
WHITENESS	>100
TYPE	UV / Latex / ECO Solvent
APPLICATIONS	Display frame system, Advertising banner



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.



Flag / Trutex 125

**trutex**  
digital printing textiles



**trutex**  
digital printing textiles

## FLAG / Trutex 125

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	115 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>150
TYPE	Sublimation Direct / Sublimation Transfer
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Flag

SUB  
Direct

SUB  
Transfer



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.





Universal Tentex / Trutex 126



## UNIVERSAL TENTEX / Trutex 126

### TECHNICAL SPECIFICATIONS


COMPOSITION	100% Polyester
WEIGHT	185 gr/m <sup>2</sup> (± 5%)
WIDTH	310 - 505 cm
WHITENESS	>100
TYPE	UV / Latex / Solvent
FLAME RETARDANCY	DIN EN 13501-1 / B-s1, d0
APPLICATIONS	Lightbox, Display Frame Systems



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.



Lightbox P / Trutex 131



## LIGHTBOX P / Trutex 131

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	130 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex / Solvent
FLAME RETARDANCY	M1 / B1 / CA 1237 Sm / NFPA 701
APPLICATIONS	Lightbox, Display Frame Systems



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited


The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



## Lightbox-S / Trutex 138



### LIGHTBOX-S / Trutex 138

#### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	120 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	DIN 4102-1 B1 / NFPA 701 Test1
APPLICATIONS	Lightbox, Display Frame Systems



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.


Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.





## Luna-S / Trutex 144



### LUNA-S / Trutex 144

#### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	120 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex
APPLICATIONS	Lightbox, Display Frame Systems



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not be given for the reasons mentioned above.



**Blackback / Trutex 146**

**trutex**  
digital printing textiles



**trutex**  
digital printing textiles

## BLACKBACK / Trutex 146

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	260 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>90
TYPE	UV / Sublimation Printing
FLAME RETARDANCY	B1
APPLICATIONS	Display Frame Systems, Roll Up

SUB  
Printing

UV



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.





## Speedy Hybrid / Trutex 147

**trutex**  
digital printing textiles



**trutex**  
digital printing textiles

### SPEEDY HYBRID / Trutex 147

#### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	190 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>110
TYPE	UV / Latex / ECO Solvent / Sublimation Transfer / Sublimation Direct
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems, Pop-up Display Systems, Blow-ups



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job


\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.





## ACOUSTIC / Trutex 148

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	220 gr/m <sup>2</sup> (± 5%)
WIDTH	310 cm
WHITENESS	>150
TYPE	UV / Sublimation Transfer / Sublimation Direct / Latex
FLAME RETARDANCY	DIN 4102-1 B1 / NFPA / BS 5867 part2 Type B
APPLICATIONS	Room climate improvement, Textile wallcoverig, Furniture coverings



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.



**Rapido N / Trutex 149**

**trutex**  
digital printing textiles



**trutex**  
digital printing textiles

## RAPIDO N / Trutex 149

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	160 gr/m <sup>2</sup> (± 5%)
WIDTH	110-160-220-260-320 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	-
APPLICATIONS	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols




The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.





**Rapido N / Trutex 149**



## **RAPIDO N / Trutex 149**


### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	150 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	-
APPLICATIONS	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.






## RAPIDO N-505 / Trutex 149

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	160 gr/m <sup>2</sup> (± 5%)
WIDTH	505 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	-
APPLICATIONS	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.




## RAPIDO N-FR / Trutex 150

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	175 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	DIN4102 / Class B-S1, D0
APPLICATIONS	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.



## SPEEDY N / Trutex 150

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	175 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	DIN4102 / Class B-S1, D0
APPLICATIONS	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.





**Blackback V / Trutex 151**



## BLACKBACK V / Trutex 151

### TECHNICAL SPECIFICATIONS


COMPOSITION	100% Polyester
WEIGHT	235 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>90
TYPE	Latex / Sub. Direct / Sub. Transfer
FLAME RETARDANCY	-
APPLICATIONS	Display Roll Up System / Stage Decoration Backdrop / Frontile / Roller Blind



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.



## Blackback J / Trutex 152



### BLACKBACK J / Trutex 152

#### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	240 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>90
TYPE	Solvent / Latex / Uv
FLAME RETARDANCY	-
APPLICATIONS	Display Roll Up System / Stage Decoration Backdrop / Frontile / Roller Blind

Solvent

Latex

UV



The information is based on the evaluation of carefully performed tests and practical experience.  
Due to the different conditions occurring during printing, test prints should be made.  
A binding assurance of the properties can not to be given for the reasons mentioned above.





Speedy Prime / Trutex 156

**trutex**  
digital printing textiles



**trutex**  
digital printing textiles

## SPEEDY PRIME / Trutex 156

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	180 gr/m <sup>2</sup>
WIDTH	160 - 260 - 320 cm
WHITENESS	>100
TYPE	UV / Latex / Solvent / Sublimation Transfer
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems, Pop-up Display Systems, Blow-ups



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.


Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.





**Black Back N UV / Trutex 158**



## BLACK BACK N UV / Trutex 158

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	240 gr/m <sup>2</sup> (±5%)
WIDTH	505 cm
WHITENESS	>90
TYPE	UV
FLAME RETARDANCY	-
APPLICATIONS	Banners, Display Frame Systems



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.