



# **trutex**

*digital printing textiles*

Mehmet Nesih Özmen Mh. Savur Sk. No:22  
Merter - Güngören - İstanbul / Turkey  
P. +90 212 637 76 68 | F. +90 212 637 03 38  
[www.ledu.com.tr](http://www.ledu.com.tr)

## SPEEDY N / Trutex 150

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	175 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	320 cm
<b>WHITENESS</b>	>100
<b>TYPE</b>	UV / Latex
<b>FLAME RETARDANCY</b>	DIN4102 / Class B-S1, D0
<b>APPLICATIONS</b>	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols



## RAPIDO N / Trutex 149

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	160 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	110-160-220-260-320 cm
<b>WHITENESS</b>	>100
<b>TYPE</b>	UV / Latex
<b>FLAME RETARDANCY</b>	-
<b>APPLICATIONS</b>	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols



## RAPIDO N / Trutex 149

### TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	150 gr/m <sup>2</sup> (± 5%)
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	-
APPLICATIONS	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols



## RAPIDO N-505 / Trutex 149

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	160 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	505 cm
<b>WHITENESS</b>	>100
<b>TYPE</b>	UV / Latex
<b>FLAME RETARDANCY</b>	-
<b>APPLICATIONS</b>	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols



## LIGHTBOX P / Trutex 131

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	130 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	320 cm
<b>WHITENESS</b>	>100
<b>TYPE</b>	UV / Latex / Solvent
<b>FLAME RETARDANCY</b>	M1 / B1 / CA 1237 Sm / NFPA 701
<b>APPLICATIONS</b>	Lightbox, Display Frame Systems



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

## HYBRID S / Trutex 160

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	175 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	320 cm
<b>WHITENESS</b>	>100
<b>TYPE</b>	UV / Latex / ECO Solvent / Sublimation Transfer / Sublimation Direct
<b>FLAME RETARDANCY</b>	-
<b>APPLICATIONS</b>	Lightbox, Display Frame Systems, Pop-up Display Systems, Blow-ups



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

## UNIVERSAL TENTEX / Trutex 126

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	185 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	310 - 505 cm
<b>WHITENESS</b>	>100
<b>TYPE</b>	UV / Latex / Solvent
<b>FLAME RETARDANCY</b>	DIN EN 13501-1 / B-s1, d0
<b>APPLICATIONS</b>	Lightbox, Display Frame Systems





## MICRO SATIN UNIVERSAL / Trutex 109

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	165 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	310 cm
<b>WHITENESS</b>	>120
<b>TYPE</b>	UV / Latex / Sub. Direct / Sub.Transfer
<b>APPLICATIONS</b>	Lightbox, Display Frame Systems



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

## FLASH ULTRA / Trutex 120

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	210 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	260-310-320 cm
<b>WHITENESS</b>	>130
<b>TYPE</b>	UV / Latex / Sublimation Direct
<b>FLAME RETARDANCY</b>	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
<b>APPLICATIONS</b>	Lightbox, Display Frame Systems



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job  
 The information is based on the evaluation of carefully performed tests and practical experience.  
 Due to the different conditions occurring during printing, test prints should be made.  
 A binding assurance of the properties can not to be given for the reasons mentioned above.

## ELASTO N / Trutex 159

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	210 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	160, 260, 320 cm
<b>WHITENESS</b>	>100
<b>TYPE</b>	DYE SUB
<b>FLAME RETARDANCY</b>	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B / M1*
<b>APPLICATIONS</b>	Decoration Elastic, Chair Covering, Decorations

Latex

SUB  
Direct

SUB  
Transfer



**PHOTO 185 / Trutex 124**  
TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	185 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	315 cm
<b>WHITENESS</b>	>100
<b>TYPE</b>	UV / Latex / ECO Solvent
<b>APPLICATIONS</b>	Display frame system, Advertising banner



## DSP-210 / Trutex 105

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	210 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	320 cm
<b>WHITENESS</b>	>140
<b>TYPE</b>	Sublimation Direct / Sublimation Transfer / Latex
<b>FLAME RETARDANCY</b>	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
<b>APPLICATIONS</b>	Display frame system, Advertising banner

Latex

SUB  
Direct

SUB  
Transfer



## BLOCKOUT / Trutex 161

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	220 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	290 cm
<b>WHITENESS</b>	
<b>TYPE</b>	Sublimation Transfer
<b>FLAME RETARDANCY</b>	
<b>APPLICATIONS</b>	Display frame system, Advertising banner



## ACOUSTIC / Trutex 148

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	220 gr/m <sup>2</sup> (± 5%)
<b>WIDTH</b>	310 cm
<b>WHITENESS</b>	>150
<b>TYPE</b>	UV / Sublimation Transfer / Sublimation Direct / Latex
<b>FLAME RETARDANCY</b>	DIN 4102-1 B1 / NFPA / BS 5867 part2 Type B
<b>APPLICATIONS</b>	Room climate improvement, Textile wallcoverig, Furniture coverings



## BLACK BACK NTR / Trutex 157

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	240 gr/m <sup>2</sup> (±5%)
<b>WIDTH</b>	320 cm
<b>WHITENESS</b>	>135
<b>TYPE</b>	UV / Sub
<b>FLAME RETARDANCY</b>	-
<b>APPLICATIONS</b>	Banners, Display Frame Systems



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



## BLACK BACK N UV / Trutex 158

### TECHNICAL SPECIFICATIONS

<b>COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	240 gr/m <sup>2</sup> (±5%)
<b>WIDTH</b>	505 cm
<b>WHITENESS</b>	>90
<b>TYPE</b>	UV
<b>FLAME RETARDANCY</b>	-
<b>APPLICATIONS</b>	Banners, Display Frame Systems



\* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

\*\* Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.